


通用控制软电缆

KVVR

导体 CONDUCTOR	符合 GB/T 3956 (idt. IEC 60332) 标准中规定的第五类裸铜导体
绝缘 INSULATION	柔性聚氯乙烯 (PVC) 混合物
芯线标识 IDENTIFICATION OF CORES	黑色芯线上附白色数字编号, 保护芯线 (如有) 采用黄绿双色芯线
成缆方式 ASSEMBLY OF CORE	单根芯线绞合成缆芯
护套 SHEATH	柔性聚氯乙烯 (PVC) 混合物, 颜色黑
额定电压 NOMINAL VOLTAGE	450/750V
试验电压 TEST VOLTAGE	3000V , 5min.
绝缘电阻 INSULATION RESISTANCE	>20MΩ·km
使用温度 OPERATING TEMPERATURE	-30 ~ +80°C (固定安装) -5 ~ +80°C (移动安装)
最小弯曲半径 MIN. BENDING RADIUS	12x 电缆外径
阻燃特性 FLAME RESISTANCE	IEC 60332.1
参考标准 REF. TO	GB/T 9330

应用/APPLICATION

KVVR电缆主要用于各类电器、仪器仪表、自动控制装置的控制信号的连接。适用于室内、要求柔软的场所。电缆的额定工作电压为450/750V。
KVVR CABLES are used for transmission control signal in application which should be expected to flexibility inquiry in door, such as Low-voltage electrical appliances, instrument, and automation control system and so on. And the rated voltage of these cables 450/750V.



通用控制软电缆

KVVR

参数表/DATA SHEET

产品编号 PART NO.	芯线数 × 标称截面积 NUMBER & NOMINAL X- SECTION AREA OF CONDUCTOR (MM ²)	外径 OVERALL DIAMETER (MM)	计算铜重 CU WEIGHT (KG/KM)
011 0102	2 × 0.5	6.6	9.6
011 0103	3 G 0.5	6.9	14.4
011 0104	4 G 0.5	7.5	19.2
011 0105	5 G 0.5	8.1	24.0
011 0107	7 G 0.5	8.7	33.6
011 0108	8 G 0.5	9.3	38.4
011 0110	10 G 0.5	10.8	48.0
011 0112	12 G 0.5	11.1	57.6
011 0114	14 G 0.5	11.7	67.2
011 0116	16 G 0.5	12.7	76.8
011 0119	19 G 0.5	13.3	91.2
011 0124	24 G 0.5	15.4	115.2
011 0127	27 G 0.5	15.7	129.6
011 0130	30 G 0.5	16.3	144.0
011 0137	37 G 0.5	17.5	177.6
011 0144	44 G 0.5	20.2	211.2
011 0148	48 G 0.5	20.5	230.4
011 0152	52 G 0.5	21.1	249.6
011 0161	61 G 0.5	22.3	292.8
011 0202	2 × 0.75	7.2	14.4
011 0203	3 G 0.75	7.6	21.6
011 0204	4 G 0.75	8.2	28.8
011 0205	5 G 0.75	8.9	36.0
011 0207	7 G 0.75	9.6	50.4
011 0208	8 G 0.75	10.3	57.6
011 0210	10 G 0.75	12.0	72.0
011 0212	12 G 0.75	12.4	86.4
011 0214	14 G 0.75	13.4	100.8
011 0216	16 G 0.75	14.1	115.2
011 0219	19 G 0.75	14.8	136.8
011 0224	24 G 0.75	17.2	172.8
011 0227	27 G 0.75	17.6	194.4
011 0230	30 G 0.75	18.2	216.0
011 0237	37 G 0.75	20.2	266.4
011 0244	44 G 0.75	22.6	316.8
011 0248	48 G 0.75	23.0	345.6
011 0252	52 G 0.75	23.6	374.4
011 0260	61 G 0.75	25.0	439.3
011 0302	2 × 1	7.4	19.2
011 0303	3 G 1	7.8	28.8
011 0304	4 G 1	8.4	38.4
011 0305	5 G 1	9.2	48.0
011 0307	7 G 1	9.9	67.2
011 0308	8 G 1	10.7	76.8
011 0310	10 G 1	12.4	96.0
011 0312	12 G 1	13.2	115.2
011 0314	14 G 1	13.8	134.4
011 0316	16 G 1	14.6	153.6
011 0319	19 G 1	15.3	182.4
011 0324	24 G 1	17.8	230.4
011 0327	27 G 1	18.2	259.2
011 0330	30 G 1	18.8	288.0
011 0337	37 G 1	20.9	355.2
011 0344	44 G 1	23.4	422.5
011 0348	48 G 1	23.8	460.9

产品编号 PART NO.	芯线数 × 标称截面积 NUMBER & NOMINAL X- SECTION AREA OF CONDUCTOR (MM ²)	外径 OVERALL DIAMETER (MM)	计算铜重 CU WEIGHT (KG/KM)
011 0352	52 G 1	24.4	499.3
011 0361	61 G 1	25.9	585.7
011 0402	2 × 1.5	8.4	28.8
011 0403	3 G 1.5	8.9	43.2
011 0404	4 G 1.5	9.6	57.6
011 0405	5 G 1.5	10.5	72.0
011 0407	7 G 1.5	11.4	100.8
011 0408	8 G 1.5	12.3	115.2
011 0410	10 G 1.5	14.8	144.0
011 0412	12 G 1.5	15.3	172.8
011 0414	14 G 1.5	16.0	201.6
011 0416	16 G 1.5	16.9	230.4
011 0419	19 G 1.5	17.8	273.6
011 0424	24 G 1.5	21.4	345.6
011 0427	27 G 1.5	21.9	388.8
011 0430	30 G 1.5	22.6	432.1
011 0437	37 G 1.5	24.4	532.9
011 0444	44 G 1.5	27.4	633.7
011 0448	48 G 1.5	27.9	691.3
011 0452	52 G 1.5	28.6	748.9
011 0461	61 G 1.5	31.0	878.5
011 0502	2 × 2.5	9.8	48.0
011 0503	3 G 2.5	10.4	72.0
011 0504	4 G 2.5	11.3	96.0
011 0505	5 G 2.5	12.4	120.0
011 0507	7 G 2.5	13.9	168.0
011 0508	8 G 2.5	15.0	192.0
011 0510	10 G 2.5	17.6	240.0
011 0512	12 G 2.5	18.2	288.0
011 0514	14 G 2.5	19.1	336.0
011 0516	16 G 2.5	20.8	384.0
011 0519	19 G 2.5	21.9	456.1
011 0524	24 G 2.5	25.6	576.1
011 0527	27 G 2.5	26.2	648.1
011 0530	30 G 2.5	27.1	720.1
011 0537	37 G 2.5	29.9	888.1
011 0544	44 G 2.5	33.6	1056.1
011 0548	48 G 2.5	34.2	1152.1
011 0552	52 G 2.5	35.5	1248.2
011 0561	61 G 2.5	37.7	1464.2
011 0603	3 G 4	11.4	115.2
011 0604	4 G 4	12.5	153.6
011 0605	5 G 4	14.1	192.0
011 0607	7 G 4	16.9	268.8
011 0703	3 G 6	12.7	172.8
011 0704	4 G 6	14.4	230.4
011 0705	5 G 6	15.8	288.0
011 0707	7 G 6	18.9	403.3
011 0803	3 G 10	17.0	288.0
011 0804	4 G 10	18.7	384.0
011 0805	5 G 10	20.6	480.1

注释/REMARK

- 1/ 更多需求可与我司联系
- 2/ X-不含黄绿芯线, G-含黄绿芯线
- 3/ 标准包装 100m、500m、1000m