


通用控制屏蔽软电缆

KVVRP

导体 CONDUCTOR	符合 GB/T 3956 (idt. IEC 60332) 标准中规定的第五类裸铜导体
绝缘 INSULATION	柔性聚氯乙烯 (PVC) 混合物
芯线标识 IDENTIFICATION OF CORES	黑色芯线上附白色数字编号, 保护芯线 (如有) 采用黄绿双色芯线
成缆方式 ASSEMBLY OF CORE	单根芯线与聚酯填充物绞合, 外绕包聚酯薄膜带成缆芯
屏蔽 SCREEN	镀锡铜丝编织屏蔽, 编织密度不小于 85%
护套 SHEATH	柔性聚氯乙烯 (PVC) 混合物, 颜色黑
额定电压 NOMINAL VOLTAGE	450/750V
试验电压 TEST VOLTAGE	3000V , 5min .
绝缘电阻 INSULATION RESISTANCE	>20MΩ·km
30MHz 转移阻抗 TRANSFER IMPEDANCE @30MHZ	≤250 Ω/km
使用温度 OPERATING TEMPERATURE	-30 ~ +80°C (固定安装) -5 ~ +80°C (移动安装)
最小弯曲半径 MIN. BENDING RADIUS	12x 电缆外径 (移动安装)
阻燃特性 FLAME RESISTANCE	IEC 60332.1
参考标准 REF. TO	GB/T 9330

应用/APPLICATION

KVVRP产品主要用于各类电器、仪器仪表、自动控制装置的控制信号的连接。适用于室内、要求柔软的场所。电缆的额定工作电压为450/750V。编织屏蔽的选择在保证产品的柔软性要求的条件下, 使电缆具备良好的电磁兼容特性。KVVRP cables are used for transmission control signal in application which should be expected to flexibility inquiry in door, such as Low-voltage electrical appliances, instruments, and automation control system and so on. And the rated voltage of these cables is 450/750V. Tinned copper braid screen is provided with a good EMC and flexible property.



通用控制屏蔽软电缆

KVVRP

参数表/DATA SHEET

产品编号 PART NO.	芯线数 × 标称截面积 NUMBER & NOMINAL X- SECTION AREA OF CONDUCTOR (MM ²)	外径 OVERALL DIAMETER (MM)	计算铜重 CU WEIGHT (KG/KM)
012 0102	2 × 0.5	7.3	25.7
012 0103	3 G 0.5	7.6	31.5
012 0104	4 G 0.5	8.3	43.4
012 0105	5 G 0.5	8.9	50.8
012 0107	7 G 0.5	9.5	63.1
012 0108	8 G 0.5	10.1	70.5
012 0110	10 G 0.5	11.6	86.7
012 0112	12 G 0.5	11.9	97.6
012 0114	14 G 0.5	12.9	109.9
012 0116	16 G 0.5	13.5	122.1
012 0119	19 G 0.5	14.1	139.2
012 0124	24 G 0.5	16.2	172.4
012 0127	27 G 0.5	16.5	188.2
012 0130	30 G 0.5	17.1	205.2
012 0137	37 G 0.5	18.9	244.1
012 0144	44 G 0.5	21.2	312.5
012 0148	48 G 0.5	21.5	333.4
012 0152	52 G 0.5	22.1	356.2
012 0161	61 G 0.5	23.3	406.4
012 0202	2 × 0.75	7.9	32.6
012 0203	3 G 0.75	8.4	46.2
012 0204	4 G 0.75	9.0	56.1
012 0205	5 G 0.75	9.7	66.3
012 0207	7 G 0.75	10.4	83.8
012 0208	8 G 0.75	11.1	94.1
012 0210	10 G 0.75	12.8	116.0
012 0212	12 G 0.75	13.6	132.2
012 0214	14 G 0.75	14.2	149.2
012 0216	16 G 0.75	14.9	166.7
012 0219	19 G 0.75	15.6	191.4
012 0224	24 G 0.75	18.0	238.0
012 0227	27 G 0.75	18.4	261.3
012 0230	30 G 0.75	19.0	285.6
012 0237	37 G 0.75	21.2	367.7
012 0244	44 G 0.75	23.6	432.2
012 0248	48 G 0.75	24.0	463.4
012 0252	52 G 0.75	24.6	495.7
012 0260	61 G 0.75	26.0	568.7
012 0302	2 × 1	8.2	42.9
012 0303	3 G 1	8.6	54.3
012 0304	4 G 1	9.2	66.5
012 0305	5 G 1	10.0	79.7
012 0307	7 G 1	10.7	102.0
012 0308	8 G 1	11.5	115.1
012 0310	10 G 1	13.6	141.8
012 0312	12 G 1	14.0	162.7
012 0314	14 G 1	14.6	184.6
012 0316	16 G 1	15.4	207.3
012 0319	19 G 1	16.1	239.2
012 0324	24 G 1	18.6	298.2
012 0327	27 G 1	19.6	328.8
012 0330	30 G 1	20.4	384.6
012 0337	37 G 1	21.9	460.6
012 0344	44 G 1	24.4	542.5
012 0348	48 G 1	24.8	583.3

产品编号 PART NO.	芯线数 × 标称截面积 NUMBER & NOMINAL X- SECTION AREA OF CONDUCTOR (MM ²)	外径 OVERALL DIAMETER (MM)	计算铜重 CU WEIGHT (KG/KM)
012 0352	52 G 1	25.4	625.2
012 0361	61 G 1	26.9	720.4
012 0402	2 × 1.5	9.2	56.9
012 0403	3 G 1.5	9.7	73.5
012 0404	4 G 1.5	10.4	91.0
012 0405	5 G 1.5	11.3	109.4
012 0407	7 G 1.5	12.2	142.2
012 0408	8 G 1.5	13.5	160.5
012 0410	10 G 1.5	15.6	198.6
012 0412	12 G 1.5	16.1	229.6
012 0414	14 G 1.5	16.8	261.5
012 0416	16 G 1.5	17.7	294.3
012 0419	19 G 1.5	18.6	341.4
012 0424	24 G 1.5	22.4	454.0
012 0427	27 G 1.5	22.9	500.1
012 0430	30 G 1.5	23.6	547.4
012 0437	37 G 1.5	25.4	658.8
012 0444	44 G 1.5	28.6	813.5
012 0448	48 G 1.5	29.1	874.8
012 0452	52 G 1.5	30.4	937.5
012 0461	61 G 1.5	32.2	1080.4
012 0502	2 × 2.5	10.6	82.3
012 0503	3 G 2.5	11.2	109.0
012 0504	4 G 2.5	12.1	136.9
012 0505	5 G 2.5	13.6	165.8
012 0507	7 G 2.5	14.7	218.6
012 0508	8 G 2.5	15.8	247.5
012 0510	10 G 2.5	18.4	306.9
012 0512	12 G 2.5	19.0	357.6
012 0514	14 G 2.5	20.7	434.4
012 0516	16 G 2.5	21.8	488.8
012 0519	19 G 2.5	22.9	567.3
012 0524	24 G 2.5	26.6	709.1
012 0527	27 G 2.5	27.2	784.6
012 0530	30 G 2.5	28.3	897.7
012 0537	37 G 2.5	31.1	1081.9
012 0544	44 G 2.5	34.8	1277.1
012 0548	48 G 2.5	35.8	1377.5
012 0552	52 G 2.5	36.7	1480.1
012 0561	61 G 2.5	38.9	1712.3
012 0603	3 G 4	12.2	156.6
012 0604	4 G 4	13.7	199.8
012 0605	5 G 4	14.9	243.5
012 0607	7 G 4	17.7	332.7
012 0703	3 G 6	13.9	219.9
012 0704	4 G 6	15.2	283.2
012 0705	5 G 6	16.6	347.0
012 0707	7 G 6	19.9	500.4
012 0803	3 G 10	17.8	352.3
012 0804	4 G 10	19.7	480.0
012 0805	5 G 10	22.2	587.2

注释/REMARK

- 1/ 更多需求可与我司联系
- 2/ X-不含黄绿芯线, G-含黄绿芯线
- 3/ 标准包装 100m、500m、1000m